













CARRARO REGULATORS		Function	Seat type	Inlet/Outlet diameters	Connections	Max rating	CV min/max	Set point min/max	Temperature min/max	Standard constructions	Suitable for:			Markets:			
											Grey	Blue	Red	O & G	B. S.	G. I.	Pwr
	<b>UBAN series</b>	Reducing	Single	From 1/2" up to 2"	Flanged and threaded	ANSI 1500	0,031 / 12,8	0,0012 / 46 barg	-196 / +300 °C	Body: Carbon & SS Spring case: Carbon & SS Diaphragm: Polychloroprene	✓	✓	✓	✓	✓	✓	✓
	<b>UBR series</b>	Reducing	Single	From 1/2" up to 2"	Flanged and threaded	ANSI 600	1 / 52,6	0,0012 / 46 barg	-196 / +300 °C	Body: Carbon & SS Spring case: Carbon & SS Diaphragm: Polychloroprene	✓	✓	✓	✓	✓	✓	✓
	<b>UBB series</b>	Reducing / Relief	Single	From 1/2" up to 1 1/2"	Threaded	ANSI 150	0,04 / 4,95	0,034 / 0,6 barg	-25 / +90 °C	Body: Carbon & SS Spring case: Carbon & SS Diaphragm: NBR	✓			✓	✓	✓	✓
	<b>UBAS-HP series</b>	Relief	Single	From 1/4" up to 1/2"	Threaded	ANSI 600	0,8 / 2,2	1 / 4 barg	-196 / +300 °C	Body: Stainless steel Spring case: Stainless steel Diaphragm: PTFE	✓	✓	✓	✓		✓	✓
	<b>UBS series</b>	Relief / Backpressure	Single	From 1/2" up to 2"	Flanged and threaded	ANSI 600	0,031 / 35	0,0012 / 46 barg	-196 / +300 °C	Body: Carbon & SS Spring case: Carbon & SS Diaphragm: Polychloroprene	✓	✓	✓	✓	✓	✓	✓
	<b>MM series</b>	Reducing / Relief / Backpressure	Single / Double	From 1" up to 20"	Flanged	ANSI 1500	6 / 850	0,0045 / 26,9 barg	-50 / +540 °C	Body: Carbon & SS Spring case: Carbon & SS Diaphragm: Polychloroprene	✓	✓	✓	✓		✓	✓
	<b>BPM series</b>	Reducing / Relief / Backpressure	Single / Double	From 1" up to 20"	Flanged	ANSI 600	6 / 850	0,0015 / 26,9 barg	-50 / +200 °C	Body: Carbon & SS Spring case: Carbon & SS Diaphragm: Polychloroprene	✓	✓	✓	✓	✓	✓	✓
	<b>AM series</b>	Reducing / Relief	Single / Double	From 1/2" up to 2"	Flanged	ANSI 300	0,84 / 30	0,5 / 7 barg	-20 / +235 °C	Body: Carbon & SS	✓	✓	✓	✓		✓	✓
	<b>AT series</b>	Temperature regulating	Single / Double	From 1/2" up to 2"	Flanged	ANSI 300	0,84 / 38	-2 / + 205 °C	-28 / +300 °C	Body: Carbon & SS	✓	✓	✓	✓		✓	✓
	<b>MAXOMATIC series E1/SPK</b>	Deluge valve	Single	From 1-1/2" up to 10"	Flanged and threaded	ANSI 150	75 / 1460	N.A.	-10 / + 80 °C	Body: Cast Iron, Carbon & SS Hydraulic loop: Copper + brass, 316 SS Diaphragm: NBR		✓		✓		✓	✓
	<b>MAXOMATIC series R1/S2</b>	Reducing / Relief	Single	From 1-1/2" up to 10"	Flanged and threaded	ANSI 150	75 / 1460	1 / 16 barg	-10 / + 80 °C	Body: Cast Iron, Carbon & SS Hydraulic loop: Copper + brass, 316 SS Diaphragm: NBR		✓		✓		✓	✓
	<b>MAXOMATIC series L1/L2/L3</b>	Level Regulating	Single	From 1-1/2" up to 10"	Flanged and threaded	ANSI 150	75 / 1460	N.A.	-10 / + 80 °C	Body: Cast Iron, Carbon & SS Hydraulic loop: Copper + brass, 316 SS Diaphragm: NBR		✓		✓		✓	✓
<ul style="list-style-type: none"> <li>Up to 20"</li> <li>Standard CV's from 0,031 to 850</li> </ul>		<ul style="list-style-type: none"> <li>Set pressures from 0,0012 to 52 barg</li> <li>Up to rating ANSI 1500 class</li> </ul>				<ul style="list-style-type: none"> <li>Temperatures from -196°C to 540°C</li> </ul>				<b>Special constructions</b> Exotic Materials: Monel / Duplex / Superduplex / Hastelloy / Inconel			LEGENDA				
													Grey	Blue	Red	O & G	B. S.

LEGENDA

Air & Process gases	Liquids	Steam
---------------------	---------	-------

O&G: Oil & Gas / B.S.: Blanketing system / G.I.: General Industry / Pwr: Power